

Sealing Compound

SEALING MATERIALS



Packing Fiber



FEATURES-SPECIFICATIONS Series SC/PF/LUBG

Sealing Materials

SC Series Sealing compound is a cement used extensively for sealing conduit to prevent the spread of explosive gases. It is non-shrinking and a secure seal is formed. SC Series resists acids, water, oil, etc. It is UL Listed for use with Killark ENY, EY, and EYS Series. Also CSA certified for use with any CSA certified sealing fitting.

Packing Fiber

Killark's Packing Fiber is made from an environmentally safe, non-asbestos material. It is easy to use and forms a positive dam to hold compound (Killark SC Type) in ENY, EY, and EYS Series fittings.

Threaded Lubricants

Two special blends of lubricants have been developed by Killark for use with threaded joints. These lubricants are to be used to prevent galling of pipe threads when threaded into a coupling, junction box, etc. They insure a quick release of undamaged male and female threads when parts are disassembled.

LUBG is a general purpose lubricant to be used in temperatures ranging from 0° to 125°F.

LUBT is a high-quality lubricant to be used in temperatures ranging from -40° to +500°F. It is recommended to be used on hazardous location lighting fixtures.

| | OUNCES REQUIRED PER FITTING | | | | | |
|----------|-----------------------------|------------------|----------|---------------|--|--|
| | PACKING FIBER | | | | | |
| HUB SIZE | ENY [®] | EYS [®] | EY/EYD | PACKING FIBER | | |
| 1/2" | 1.5 oz. | 3.0 oz. | 1.0 oz. | 1/16 oz. | | |
| 3/4" | 2.0 oz. | 3.0 oz. | 2.0 oz. | 1/8 oz. | | |
| 1" | 3.0 oz. | 8.0 oz. | 4.5 oz. | 1/4 oz. | | |
| 1-1/4" | 6.5 oz. | 8.5 oz. | 7.5 oz. | 1/2 oz. | | |
| 1 1/2" | 8.5 oz. | 17.5 oz. | 12.0 oz. | 1 oz. | | |
| 2" | 15.0 oz. | 27.0 oz. | 24.0 oz. | 2 oz. | | |
| 2-1/2" | _ | 42.0 oz. | 44.0 oz. | 3 oz. | | |
| 3" | _ | 47.0 oz. | 44.0 oz. | 4 oz. | | |
| 3-1/2" | _ | 56.0 oz. | 75.0 oz. | 6 oz. | | |
| 4" | _ | 56.0 oz. | 75.0 oz. | 9 oz. | | |

① ENY/EYS suitable for both horizontal or vertical applications.

| SEALING COMPOUND | | | |
|------------------|--------------|--|--|
| CATALOG NUMBER | SIZE PACKAGE | | |
| SC-4 OZ | 4 oz. | | |
| SC-8 OZ | 8 oz. | | |
| SC-1 LB | 1 lb. | | |
| SC-5 LB | 5 lbs. | | |

| PACKING FIBER | | | | |
|----------------|--------------|--|--|--|
| CATALOG NUMBER | SIZE PACKAGE | | | |
| PF-2 | 2 oz. | | | |
| PF-4 | 4 oz. | | | |
| PF-16 | 1 lb. | | | |

| THREAD LUBRICANTS | | | | |
|-------------------|-------------------|--|--|--|
| CATALOG NUMBER | CONTAINER PACKAGE | | | |
| LUBT-2 | 2 oz. | | | |
| LUBG-6 | 6 oz. | | | |



